

SPECIFICATIONS FOR CONFERENCE TABLE PER SEATER

1. Work surface: Made of at least 25 mm Thick Pre-laminated twin board of E1-P2 grade and approved shade, per seater to be required for 40 people in the different module as per the approved layout conforming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping.
2. Understructure: It consists of an 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade conforming to IS-12823:1990.
3. Edge banded with matching 2 mm thick PVC lipping.
4. Aluminum alloy 63400 - WP profile is used for connecting panels together.
5. The product has a knock-down construction. Module
6. Plastic ABS access flap is provided for easy access to wires and cables. The worktop is available in various shapes as shown above.
7. Modesty Panel: Made of 18mm Thick Pre-laminated twin board of E1-P2 grade and approved shade conforming to IS-12823:1990, Edge banded with matching 2 mm thick PVC lipping. Powder-coated accent metal strip is provided below the work surface to enhance aesthetics. It is made of 0.8mm CRCA as per IS 513, epoxy polyester powder coated (DFT 40-60 microns)
8. Wire Management: An array of panels made of 0.8mm CRCA MS IS: 513, epoxy polyester powder coated (DFT 40-60 microns) is used for the flow of wires and cables.
9. Product Should be BIFMA Level and UL Green guard certified and OEM should
10. Cutout on top with two-piece injection moulded plastic part polymer component is fitted to pull out audio, and video cables onto the worktop and connect devices charger to power socket below worktop.).
11. Product should carry the UL Green guard certificate and should reflect on the website for validation, the certificate along with the test report, OEM specification sheet and reference image to be attached to the technical bid. Which could be verified at the time of the technical bid.
12. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, ISO13485, BIFMA Level at least one product reflecting on the website, AIOTA, and UL green guard certification.

